

CELESTION
INSIDE



SPECIFICATION

MODEL	CSP-108	CSP-110	CSP-112	CSP-115	CSP-112M
Components	1 x 8" TF0818 (LF Driver, Voice Coil 45mm) 1 x 1" CDX1-1445 (HF Compression Driver, Voice Coil 35mm)	1 x 10" TF1020 (LF Driver, Voice Coil 50mm)	1 x 12" TF1225 LF Driver, Voice Coil 64mm 1 x 1" CDX1-1446 (HF Compression Driver, Voice Coil 35mm)	1 x 15" TF1525 (LF Driver, Voice Coil 64mm)	1 x 12" TF1225 (LF Driver, Voice Coil 64mm) 1 x 1" CDX1-1747 (HF Compression Driver, Voice Coil 44mm)
Frequency Response	70Hz - 20kHz	60Hz - 20kHz	60Hz - 20kHz	60Hz - 20kHz	60Hz - 20kHz
Dispersion	50° to 100° Horizontal x 55° Vertical	50° to 100° Horizontal x 55° Vertical	70° Horizontal x 40° Vertical	70° Horizontal x 40° Vertical	50° to 100° Horizontal x 55° Vertical
Power Handling	100Wrms / 200W Music Program	150Wrms / 300W Music Program	250Wrms / 500W Music Program	250Wrms / 500W Music Program	250Wrms / 500W Music Program
Sensitivity 1W @ 1M	94dB	97dB	97dB	97dB	97dB
Maximum SPL	114dB Continuous, 117dB Peak	119dB Continuous, 122dB Peak	121dB Continuous, 124dB Peak	121dB Continuous, 124dB Peak	121dB Continuous, 127dB Peak
Nominal Impedance	8Ω				
Construction	15mm Medium-Density Fibreboard Enclosure				15mm PU Painted Plywood Enclosure
Connectors	2 x NL4MP Speakons 4 pole (pin 1+ 1-: Full Range / pin 2+ 2-: NC)				
Dimensions (WxHxD)	250x475x285mm	330x530x340mm	400x670x455mm	450x765x455mm	400x665x400mm
Net Weight	10.4kg(22.88lbs)	14.5kg(31.9lbs)	22.6kg(49.72lbs)	25.4kg(55.88lbs)	21kg(46.2lbs)

INSTALLATION



- Eyebolt M8
Eyebolt M8 x 15 For CSP-108, CSP-110
Eyebolt M8 x 30 For CSP-112, CSP-112M, CSP-115



การใช้งานแบบที่ 3 Fixed Installation

สามารถแขวนติดตั้งถาวรหรือชั่วคราวโดยใช้ Eyebolt M8x30 และ Shackle ในการแขวนกับสลิงเพื่อรับองศา การกระจายเสียงทางแนวตั้งและแนวนอนได้

การใช้งานแบบที่ 1 Stand Mountable

ใช้ติดตั้งบนขาตั้งลำโพง สำหรับงานประกาศสินค้า หรืองาน Event ทั่วไ เพื่อ ให้เสียงสามารถกระจายได้ ทั่วถึง



การใช้งานแบบที่ 2 Stage Monitoring

ใช้เป็นลำโพงมอนิเตอร์บนเวที

