

H-SERIES

INDOOR / OUTDOOR SET-UP LOUDSPEAKER

NTS



TECHNICAL SPECIFICATION

■ H-3 / H-3T

Rated power	15W RMS
Power [MAX]	25W
Bass speaker	3"
Speakers	0.75"
Connections	2-pole terminal
Sensitivity	83dB
Impedance	8Ω
Frequency-range	100Hz ~ 18KHz
Dimension [HxWxD]	165x115x165 mm.
H-3T Line Transformer	2/4/8/12 W (100V)

■ H-5 / H-5T

Rated power	35W RMS
Power [MAX]	75W
Bass speaker	5"
Speakers	1"
Connections	2-pole terminal
Sensitivity	89dB
Impedance	8Ω
Frequency-range	60Hz ~ 20KHz
Dimension [HxWxD]	256x167x218 mm.
H-5T Line Transformer	2/4/8/16 W (100V)

■ H-8 / H-8T

Rated power	85W RMS
Power [MAX]	125W
Bass speaker	8"
Speakers	1"
Connections	2-pole terminal
Sensitivity	90dB
Impedance	8Ω
Frequency-range	45Hz ~ 20KHz
Dimension [HxWxD]	360x240x254 mm.
H-8T Line Transformer	4/8/16/30 W (100V)