

Mixing Amplifier

Model: PM-8500





System Features

- Standard 19" 2U metal housing with front panel of aluminium alloy.
- ► Built-in players of USB card,FM tuner and bluetooth receiver.
- High-definition display for the working status of playing programmes.
- Powerful amplifier tubes.
- → 3 microphone inputs,2 AUX inputs and 1 AUX Output.
- 70/100-volt and 4 to 16 ohms(Ω) output loads.
- Individual volume controller for inputs.
- Master volume controller for all inputs.
- BASS and TREBLE tone controllers.
- Features muting function that MIC1 input overrides others of
 - ► MIC2,MIC3,AUX1,AUX2 with 0~30dB attenuation.
- Protections of short circuit, overload, high temperature.
- Includes a line level output for adding additional amplifiers.
- Includes Remote Control to control Media Player





Mixing Amplifier

Model: PM-8500

Specification

	500W
Low impedance	4-16Ω
70V	10Ω
100V	20Ω
	0.775V (0dBV)
MIC 1,2,3	600Ω, 10-15mV (unbalanced)
AUX 1,2	10KΩ, 200-470mV (unbalanced)
•	20Hz-20KHz (±3dB)
	<0.5% at 1KHz, 1/3 rated output power
MIC 1,2,3	≥72dB
AUX 1,2	≥85dB
Bass	±10dB at 100Hz
Treble	±10dB at 12KHz
	MIC1 overrides other input signals at 0~30dB
	Volume, tone/treble, mute, power
	AC fuse, Overload, Short circuit, high temperature
	FUSE×8A
	DC 12V FAN
	AC: POWER, level: 2、4、6、8、10
	AC220~240V, 50-60Hz
	675W
	(3×0.75 mm2)×1.5M (standard)
	89(H)×483(W)×366(D)
	185(H)×520(W)×435(D)
	15.5
	17.20
	70V 100V MIC 1,2,3 AUX 1,2 MIC 1,2,3 AUX 1,2 Bass

