



2 WAY SPEAKER

Model : SP-65BT

PRODUCT DESCRIPTION

The SP-65T Speaker are compact two-way speaker systems designed for high efficiency, wide range, and high power input handling capability. These speaker systems can be installed in a manner ideal for the location and intended application.

FEATURES

- Tasteful design optimized for most building interiors and semi-indoor installations
- Compact set powerful 6 inch woofer and 2 inch dome tweeter
- Overload Protection Circuitry
- U Shape hanger for setup to wall either horizontally or vertically
- Selectable impedance (100V : 30W,16W,8W), (70V : 15W, 7W, 5W) and low impedance (8Ω)
- Weather-resistant



TECHNICAL SPECIFICATION

Enclosure	2-way bass reflex type
Rated Input	Continuous : 60W , Maximum : 80 W
Impedance	8 Ω : 80 W 100V AC Line : 30W ,16W, 8W 70V AC Line : 15W , 7W, 5W
Sensitivity	98 dB @ 1W: 1m
Frequency Response	20 - 20,000 Hz
Maximum SPL (1m)	104 dB ± 2dB
Speaker Components	6 inch (15.24 cm.) Dynamic cone-type speaker x1 2 inch (5.08 cm.) dome tweeter x1
Material/ Finish (Enclosure)	ABS resin
Water Protection	IPX4
Bracket	U Shape , Steel with Powder Coating for Vertical or Horizontal hanging
Dimensions	20.5 x 28.5 x 18.0 cm.

Manufactured and Distributed by

TTN Pro LIMITED PARTNERSHIP
No.32 Arun-Aummarin Rd. Kanlaya Thonburi Bangkok 10600 THAILAND
Tel +6681-804-1100 ; Email kct47@me.com