

GL-SERIES

STEREO MIXER WITH 99 DSP EFFECT & USB

NTS



- GL-8 : 8 Channel (4 Mono / 2 Stereo) with 99 DSP Effect & USB
- GL-12 : 12 Channel (4 Mono / 4 Stereo) with 99 DSP Effect & USB
- GL-16 : 16 Channel (8 Mono / 4 Stereo) with 99 DSP Effect & USB

TECHNICAL SPECIFICATION

- Insert point on mono input
- 3 band EQ with sweepable midrange on mono input
- 4 band EQ on stereo input
- 1 Aux send for external effects and monitoring
- Peak LED on all input
- LOW CUT switch on mono input
- MUTE and SOLO switch on all input
- Built in 99 program digital effect
- USB interface for MP3 input and playback with digital display
- 9 band graphic EQ
- Stereo output and 2 group output
- +48V phantom power supply

MAIN SPECIFICATION :

Channel Mic/Line	8 CH : 4 Mono/2 Stereo [GL-8]	
.....	12 CH : 4 Mono/4 Stereo [GL-12]	
.....	16 CH : 8 Mono/4 Stereo [GL-16]	
Frequency Response	20Hz - 20KHz	
T.H.D.	≤ 0.05%	
Signal to Noise Ratio	≥ -103dB	
Mono Channel EQ : High	+/-15dB, 12KHz	
.....	: Mid ... +/-15dB, sweepable 100Hz to 8KHz	
.....	: Low	+/-15dB, 80Hz
Stereo Channel EQ : High	+/-15dB, 12KHz	
.....	: High - Mid	+/-15dB, 3KHz
.....	: Low - Mid	+/-15dB, 500Hz
.....	: Low	+/-15dB, 80Hz
Power Requirement	AC 100V to 240V, 50/60Hz	