

HX-Series

Power Amplifier



Back

SPECIFICATIONS

MODEL

HX-2500

HX-2600

HX-21400

STEREO (2 CHANNELS)

8 Ω /FTC 20Hz - 20KHz Ω 0.5% THD

4 Ω /FTC 20Hz - 20KHz @ 0.5% THD

S/N (20Hz - 20KHz) 8

THD (@ 8 Ω 1KHz)

INPUT IMPEDANCE

FREQUENCY RESPONSE

CIRCUIT TYPE

DAMPING FACTOR

COOLING SYSTEM

INPUT/OUTPUT CONNECTION

CONTROL

PROTECTION

POWER SUPPLY

DIMENSIONS (WxDxH)

PACKING DIMENSIONS (WxDxH)

NET WEIGHT

GROSS WEIGHT

POWER FOR EACH CHANNELS

250W

350W

800W

500W

600W

1400W

99dB

< 0.5%

35K Ω (BALANCED)

20Hz - 20KHz @ 1W

CLASS AB

> 300 @ 8 Ω

ALL 2 Fan

INPUT : Balance Female XLR

OUTPUT : Balance Male XLR

Volume Control For Each Channel , Stereo / Parallel

Low Cut , Crossover For 1&2 Channels

NORMAL : Active , SIG : Signal , PRO : Protect (Clip)

Short , Auto Limited , Over Load AC/DC Protection

220V AC/50HZ

483 x 435 x 98 MM.

555 x 542 x 120 MM.

12.6 KG. (27.97 lbs)

14.6 KG. (32.41 lbs)

18.1 KG. (48.18 lbs)

15KGS

17KGS

20.5KGS