



Center Control Unit

Model : H-8700M



System Features

- ▶ Infra-red transmission technology guarantees privacy
- ▶ Support Mode : Limit (1/2/3) , FIFO (1/2/3) and Chairman Only
- ▶ Support video camera auto-track with video processor
- ▶ 160x32 dot matrix LCD display system information
- ▶ Two group audio output interface : 1 AF Out , 1 Line Out
- ▶ Installation : 19 inch frame
- ▶ OLCD display current mode ,online microphone number ,activity microphone number and ID
- ▶ LED indicator: Data communication indicator, if main unit data communication properly, the blue LED will flashing rhythmically , separate 4 channels
- ▶ Audio channel indicator (first channel for chairman mic, others for delegate)
- ▶ Audio Level Control.
- ▶ Antenna built-in
- ▶ Admin card Interface for admin to control the system
- ▶ Designed accordance to UL and CE Standard
- ▶ If main unit turn-off power , microphone will shut off the power within 60 seconds.

Specification

▶ Transmission Method	Wireless infrared
▶ IR transceiver connection interface	8 Inputs
▶ Output	AF-out ,XLR
▶ External video processor connection interface	RS-485
▶ RS232 data control interface	PC , Central Control System
▶ Power supply	AC110V-240V/50 Hz-60 Hz
▶ Frequency response	30Hz -20 KHz
▶ T.H.D>	<0.05%
▶ Power supply	AC110V-240V/50 Hz-60 Hz

Distributor

V.C.M. ELECTRONIC SOUND PROJECT LIMITED PARTNERSHIP
 No.20 Prapitak Rd. Wangburapapirom Pranakorn Bangkok 10200 THAILAND
 email:vcmaudio1@gmail.com
 Line@:vcmaudio

