



PE-304/604/BU/WU

Pendant speaker



Ultra lightweight for
high-ceiling venues.

PE-304/604/BU/WU

Pendant speaker

These pendant speakers are ABS resin bass-reflex enclosure with a 12 cm (5") cone-type woofer and a balanced-dome tweeter. They are intended to be installed suspended from a ceiling – they are very lightweight, with a stylish design inspired by modern lighting fixtures, allowing them to harmoniously blend in with a room design.

- Remarkably lightweight with stylish design inspired by modern lighting fixtures
- Ideally suited for BGM & announcements
- 8 Ω and 25V/70V/100V operation
- Input impedance is easily changed with a rotary switch on the top of the speaker
- With speaker cable, GRIPPLE® hanging wire & safety wire pre-attached, for faster, easier and more secure installation

Application examples



Airports



Factories



Shopping malls



Office buildings

Specifications



| | PE-304BU/304WU | PE-604BU/604WU |
|-----------------------|--|--|
| Enclosure | | Bass-reflex type |
| Rated Input | 30W (100V, 70V line, 8Ω), 3.7W (25V line) | 60W (100V, 70V line, 8Ω), 7.5W (25V line) |
| Rated Impedance | 100V line: 330Ω (30W), 1kΩ (10W), 3.3kΩ (3W), 10kΩ (1.3W) 70V line: 170Ω (30W), 330Ω (15W), 1kΩ (5W), 3.3kΩ (1.5W), 10kΩ (0.6W) 25V line: 170Ω (3.7W), 330Ω (1.9W), 1kΩ (0.6W), 3.3kΩ (0.2W), 10kΩ (0.1W) Low impedance: 8Ω | 100V line: 170Ω (60W), 330Ω (30W), 670Ω (15W), 3.3kΩ (3W) 70V line: 83Ω (60W), 170Ω (30W), 330Ω (15W), 670Ω (7.5W), 3.3kΩ (1.5W) 25V line: 83Ω (7.5W), 170Ω (3.7W), 330Ω (1.9W), 670Ω (0.9W), 3.3kΩ (0.2W) Low impedance: 8Ω |
| Sensitivity (1W, 1m) | 90dB (330Hz – 3.3kHz, pink noise) | |
| Frequency Response | 95Hz – 20kHz (–10dB) | 110Hz – 20kHz (–10dB) |
| Speaker Component | 12 cm (5") cone-type + balanced-dome tweeter (coaxial) | |
| UL Code | UL1480 UUMW, ULC-S541 | |
| Operating temperature | –10°C to +50°C | |
| Finish | PE-304BU: Enclosure: ABS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-304WU: Enclosure: ABS resin, white (RAL 9010 equivalent); Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint | PE-604BU: Enclosure: ABS resin, black Grille: Surface-treated steel plate mesh, black, paint PE-604WU: Enclosure: ABS resin, white (RAL 9010 equivalent) Grille: Surface-treated steel plate mesh, white (RAL 9010 equivalent), paint |
| Dimensions | ø186 x 275 (H) mm (ø7.32" x 10.83") (not including wires and cable) | |
| Weight | 2kg (not including wires and cable) | 2.9kg (not including wires and cable) |
| Accessory | GRIPPLE® No. 1 x 1, GRIPPLE® No. 2 x 1, Release key (for GRIPPLE®) x 1, Safety wire (ø1.5mm (ø0.06")) x 1, Hanging wire (ø2mm (ø0.08")) x 1, Speaker Cable (4-core FPL listed cable 4.6m (15.09ft) x 1 | |

*GRIPPLE® No. 1 and GRIPPLE® No. 2 are hangers for suspending the speaker. GRIPPLE® is a registered trademark of Gripple Limited, England.