

M-44DT-AM

DANTE AUDIO INTERFACE



A Dante audio interface with 4 inputs and 4 outputs that seamlessly connects amplifiers, mixers, digital microphones, and other devices on a Dante network. It can be mounted in an EIA standard equipment rack with the rack mounting panel MB-M44DT (optional).

Key features

- 4 inputs
- 4 outputs
- individual gain controls
- rack mountable

Specifications

Power Source	100 - 240 V AC, 50/60 Hz (use of the supplied AC adapter)
Current Consumption	10W
Input	Input 1-4: -50 - 0 dBV, 4.4 k Ω , electronic balanced, removable terminal block
Output	Output 1-4: 0 dBV, 10 k Ω , electronic balanced, removable terminal block
Frequency Response	20 - 20,000 Hz, ± 3 dB
Total Harmonic Distortion	0.01% (LPF 20 kHz)
Network Protocol	100Mbps, RM II
Operating Temperature	0°C to +40°C (32°F to 104°F)
Operating Humidity	90% RH or less (no condensation)
Finish	Panel: Aluminum, black, alumiteCase: Surface-treated steel plate, black, paint
Dimensions	130 (W) X 44 (H) X 161 (D) mm (5.12" X 1.73" X 6.34")
Weight	0.81 kg (1.79 lbs)
Included Accessories	AC Power adpopter x1, Removable terminal plug (6 pins) x4

Product rear image



Dimensions