



Accessories

Model : H-2400 Series

Model : H-2400T



Features

- 2.4 GHz AFHS Wireless Meeting System Antenna Panel

Carrier Frequency	2.4G (2400-2483MHz)
Audio Channel	4 (1 Chairman + 3 Delegate)
Spread Spectrum	Spread Spectrum
Transmitting Power	<20dBm
Frequency response	50Hz-15KHz
Power Supply	230V/50Hz~60Hz
Consumption Rating	7W
Receiving sensitivity	-83dBm
S/N	95dB
Dimensions (mm)	483 x 377 x 88, 2 U rack 19"

Model : H-2288B



Features

- Power Supply : 110V-240V/ 50Hz~60Hz
- Max Charging current of each unit : 700 mA
- Charging Status : Red LED Flashing-Charging
Green LED-Full Charged
- Dimension & N.W : 400x380x150 mm , 9 kg.
- With Hard Case for protection
- Handle and wheel for movement

Power supply	110V-240V/50Hz~60Hz
Consumption rating	200W
Charge quantity	16
MAX charging current of each	700mA
Charging time	About 8~10 hours
Charging status	Red LED flashing - charging, Green LED - full
Operating temperature range	0-40 degree
Dimension (mm)	620x370x175
Net weight (Kg)	9.0

Distributor

V.C.M. ELECTRONIC SOUND PROJECT LIMITED PARTNERSHIP
No.20 Prapitak Rd. Wangburapapirom Pranakorn Bangkok 10200 THAILAND
email:vcmaudio1@gmail.com
Line@:vcmaudio

