



MIXING AMPLIFIER

Model : TL-60W

PRODUCT DESCRIPTION

The basic public address mixer amplifiers. It is featured of 3 balanced microphone inputs, 2 aux inputs and 1 EMC input. Priority muting is achieved via EMC for overriding other inputs except Mic1 on front panel. Individual gain controls are provided for Mic 1-3 and Aux 1-2, bass and treble controls and master volume control are provided for overall tone control. 70V, 100V and low impedance 4-16ohms speaker outputs are provided. Extensive protection from short-circuit, overload and high temp.



FEATURES

- Mixer amplifier for paging and background music system
- Rated power 60W
- VU Meter (LED Display) show the signal
- 70V, 100V and low impedance 4-16ohm speaker output
- Three balanced Mic input
- Mic 1(phone jack) with VOX priority and VOX level on front panel to reduce all signals.
- Mic 2-3 by XLR type on rear panel with phantom power
- Two Aux Inputs and 2 line inputs for spare use
- One EMC priority input
- Mic 1-3, Aux 1-2 and master volume controls and bass/treble tone control
- Signal for short circuit protection, overload and high temp protection (AC Fuse, DC voltage overload)

TECHNICAL SPECIFICATION

Power Supply	AC 220 - 240 V / 50-60Hz
Rated Power Output	60W
Inputs	3 Mic (Phone Jack x 1 , XLR x 2 "Phantom Switch") , 2 AUX
Outputs	4-16 Ω , 70V, 100V and COM 1 Mix Output (AUX OUT) for Recording
Frequency Response	80Hz - 16 kHz \pm 3dB
THD @ 1 kHz	less than 1%
S/N ratio	MIC : 66 dB AUX : 80 dB
Dimensions	19" / 2U
Weight	12 kg.

Manufactured and Distributed by

TTN Pro LIMITED PARTNERSHIP
No.32 Arun-Aummarin Rd. Kanlaya Thonburi Bangkok 10600 THAILAND
Tel +6681-804-1100 ; Email kct47@me.com

