



FUNCTIONS

- Recording
- Responsive 3 Band EQ
- Channel and Master Meters
- 60mm Dust Protected Faders
- 2-Track Monitoring and Replay to LR
- Headphones and Local Monitor Outputs
- Digital Effect Processor
- Built-in Strong Power Amplifier With Complete Protection Function



มีช่องเสียบ

USB/MP3/WAV PLAYER/RECORDER

SPECIFICATIONS

MODEL	ST-402P	ST-602P	ST-1002P
INPUT	4 Mono 2 Stereo	6 Mono 2 Stereo	10 Mono 2 Stereo
OUTPUT POWER	300 W x 2	300 W x 2	500 W x 2
MAXIMUM INPUT LEVEL	MIC + 24dBu, Line + 24dBu, Other Line + 20dBu		
MASTER METERS	12 Segment-30dB to CLIP		
CHANNEL METERS	1 LED Signal Indication		
FREQUENCY RESPONSE	20Hz to 30kHz 0.5dB		
CMRR (MIC 1kHz)	>75dB		
THD+N	<0.01%(Channel to Mix Out)		
CROSS TALK at 1kHz	Fader Shutoff >85dB, Mute Shutoff >85dB Inter Channel >82dB		
NOISE, RMS 22 Hz to 22kHz	EIN -122dBu, Residual Output Noise <-90dBu L/R Main Mix Noise <-82dBu, Aux Mix Noise <-82dBu		
STEREO CHANNEL	TRS Unbalanced, Tip Hot, 10kOhm, Sensitivity -40 to +h14 dBu		
L/R OUTPUT	XLR Balanced, Pin 2 Hot, <75 Ohm, +4 dBu, Max + 22 dBu		
HEADPHONES	TRS, Tip L, Ring R, 30 to 600 Ohm Headphones Recommended		