

DH-110 / DH-120 Specifications

STARIGHT HORN SPEAKER DH-110



(DHA-11 + DH-11B)

	DH-110
Applicable Drivers	TU-631/631M, TU-632/632M, TU-651/651M. TU-652/652M, TU-660/660M
Sensitivity	110 dB (1 W, 1 m) (When operated with a driver.)
Frequency Response	180 Hz - 6 kHz (When operated with a driver.)
Driver Coupling	1 - 3/8 18 threads (inch screw)
Variable Installation Angle	Vertical: +10°, -20° (when locally procured mounting bracket is used)
Finish	Horn A: Aluminum, ivory, powder coating L-shaped Adapter and Horn C: Aluminum, ivory, powder coating Bracket: Steel plate, ivory, powder coating
Dimensions	ø518 x 968 (D) mm (ø20.40" X 38.11")
Weight	5.3 kg (11.69 lb)
Accessory	Stainless steel bolt for assembly x 1 set, Gasket x 1 set, Anti-bird net x 1 set

STARIGHT HORN SPEAKER DH-120



(DHA-11 + DH-12B)

	DH-120
Applicable Drivers	TU-631/631M, TU-632/632M, TU-651/651M. TU-652/652M, TU-660/660M
Sensitivity	110 dB (1 W, 1 m) (When operated with a driver.)
Frequency Response	180 Hz - 6 kHz (When operated with a driver.)
Driver Coupling	1 - 3/8 18 threads (inch screw)
Variable Installation Angle	Vertical: +10°, -20° (when locally procured mounting bracket is used)
Finish	Horn A: Aluminum, ivory, powder coating L-shaped Adapter and Adapter: Aluminum, ivory, powder coating Bracket: Steel plate, ivory, powder coating
Dimensions	ø518 x 884 (D) mm (ø20.40" X 34.80")
Weight	5.3 kg (11.69 lb)
Accessory	Stainless steel bolt for assembly x 1 set, Gasket x 1 set, Anti-bird net x 1 set

Diaphragms & Driver Unit Cover



	Dome Diaphragm DG-30DB
Rated Input	50W
Rated Impedance	16Ω
Sensitivity	110dB (1W, 1m)
Frequency Response	150Hz - 6kHz
Applicable Driver Unit	TU-631/631M, TU-632/632M, TU-651/651M. TU-652/652M



	Ring Diaphragm
Rated Input	60W
Rated Impedance	16Ω
Sensitivity	110dB (1W, 1m)
Frequency Response	150Hz - 8kHz
Applicable Driver Unit	TU-660 / 660M



	UC-200A
Finish	Unit Cover: Glass fiber mixed unsaturated polyester resin, ivory Cover Fixing Screw: Stainless Steel
Weight	590g
Accessory	Washer x 2, Throat gasket x 1
Applicable Driver Unit	TU-631/631M, TU-632/632M, TU-651/651M. TU-652/652M, TU-660/TU-660M
Applicable Horn	TH-650, TH-660, TH-652, DH-110, DH-120