



THE UNIVERSE OF INSTALLATION

น้ำเสียงที่คมชัดคือปัจจัยหลักของ SHOW

MPA-60RT

Multiplex Professional Amplifiers



Back



Back

MPA-120RST | MPA-240RST

Multiplex Professional Amplifiers

SPECIFICATIONS

MODEL	MPA-60RT	MPA-120RST	MPA-240RST
POWER OUTPUT	60 W	120 W	240 W
FREQUENCY RESPONSE	80 Hz - 16 KHz (±3 dB)		
POWER SUPPLY	AC 220 V / 240 V 50 Hz / 60 Hz ; DC 24 V		
INPUT / SENSITIVITY	MIC : -52dBv Balanced ; Phantom : -52dBv / 24 V Balanced ; Line : -10dBv Unbalanced ; AUX : -6dBv Balanced ; AMP. in : 0dBv Unbalanced ; Tel : -10dBv Balanced		
HARMONIC DISTORTION	</=1%		
S/N RATIO	MIC : >= 65dB ; AUX : >= 80dB ; Phone : >= 65dB ; Line : >= 75dB		
OUTPUT	Com, 4Ω, 25V, 70V, 100V		
ZONE OUTPUT	-	Zone 1 -4 : 100V	
CONTROLS	3 Input Volume Controls, 1 AUX Volume Controls, 2 Treble / Bass Controls, 1 Master Volume Controls, 1 Tel. Input Volume Controls, 3 REC Selector Switch	4 Input Volume Controls, 1 AUX Volume Controls, 2 Treble / Bass Controls, 1 Master Volume Controls, 1 Tel. Input Volume Controls, 3 REC Selector Switch 4 Zone Out Volume Controls,	
FUNCTION	USB/SD/TURNER/RECORDING/Phantom		
DIMENSION (W x D x H)	420 x 330 x 88 mm		