



Features

- * Unique patented technology, specially designed anti-RF radio frequency interference tube, which can completely eliminate the noise, Showing a perfect high-level conference environment.
- * Unique patented design, Fully embodies the designer to grasp the vision of the world aesthetics.
- * Unique microphone head design, So that even if the speaker does not have the cotton cover, but also completely eliminate the "pupu" low-frequency impact.
- * Professional heart-shaped condenser microphone core, Very high sensitivity and voice clarity; And with a ring of red & green indicator light when speaking.
- * When the red ring light is on, it means somebody is speaking; when green is on, it means apply for awaiting speech.
- * It has function of suppress whistle, when microphone is open, the built-in speaker will be closed automatically.
- * Built-in speaker, headset jack, which can adjust the headset volume.
- * Use the professional 8 core aviation plug by cascading units, and with the metal fixed nut to avoid loosening and falling.
- * It has 1.8m 8 core connection line that is used full line of aluminum foil and waterline shield, which greatly reduce the interference of strong electromagnetic waves on the wire, avoid "zizi" noise.
- * The address code of each unit can be adjusted at any time to facilitate the construction.
- * It is passive equipment, which is powered by the system controller, input voltage is 24V; belongs to the safe scope.
- * Chairman unit has no limited by speakers qty.
- * Chairman unit has priority function of taking full control of the order of the meeting, can approve or reject the application for a delegate unit.
- * The Chairman unit connection position is not limited; can be connected in any position of circuit.
- * "Hand-in-hand" Cable cascade mode, which is easy to install and maintain.
- * There are 5 multi-functional buttons for voting, election and meeting evaluation.
- * The button indicator has a prompt for real-time voting.
- * Speaking unit can apply or cancel to speak;
- * LCD display can show the operation of the vote, voting mode, to avoid mistakes.

Specifications

Model	TS-0622
Microphone Type	Heart-oriented directional electret
Frequency Response	80Hz~16KHz
Microphone Input Impedance	1K Ω
Sensitivity	-46 dBV/Pa
Max SPL	100dB(THD>3%)
SNR	>80dB
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Max Power Consumption	2.5W
Headphone Load	8-32 Ω
Headphone Volume	Max 40mW
Headphone Interface	3.5mm Headphone monaural jack
Follow Standard	IEC60914
Connector	1.8m aviation 8 core cable
Hand-in-hand Expansion Port	Unavailable
Power Supply Mode	Controller power supply DC24V
Voting Function	5/3 keys to vote
Sign-in Function	Button sign-in
Color	Silver
Display	Chinese and English font full dot matrix LCD display
Weight	0.9kg
Display Screen	LCD blue screen blue on white
Microphone Height	460mm
Dimension(mm)	225(L) \times 131(W) \times 48(H)
Installation Method	Tabletop