

CS-1CH

Order No. 0173070

Microphone station for chairperson

- Back electret cartridge with cardioid polar pattern, optimised for voice transmissions
- Low-distortion speaker
- Reproduction via optional headphones
- Large function button
- Status displays at microphone and desktop station
- Priority button allows to interrupt an ongoing discussion between conference delegates, alternatively with a chime

| Model | CS-1CH |
|-----------------------|--|
| Polar pattern | cardioid |
| System | back electret |
| Audio frequency range | 50-18,000 Hz |
| Power supply | via control unit CS-1CU |
| Gooseneck length | 400 mm |
| Dimensions | 115 x 65 x 170 mm (console housing) |
| Weight | 1.1 kg |
| Cable | 2 m |
| Connection | 2 x 3.5 mm jack 1 x 2 m connection cable with 7-pole DIN plug 1 x 7-pole DIN jack |

**CS-1DU**

Order No. 0173080

Microphone station for conference delegates

- Back electret cartridge with cardioid polar pattern, optimised for voice transmissions
- Low-distortion speaker
- Operation via function button
- Headphone connection
- Status displays at microphone and desktop station

| Model | CS-1DU |
|-----------------------|--|
| Polar pattern | cardioid |
| System | back electret |
| Audio frequency range | 50-18,000 Hz |
| Power supply | via control unit CS-1CU |
| Gooseneck length | 400 mm |
| Dimensions | 115 x 65 x 170 mm (console housing) |
| Weight | 1.1 kg |
| Cable | 2 m |
| Connection | 2 x 3.5 mm jack 1 x 2 m connection cable with 7-pole DIN plug 1 x 7-pole DIN jack |

**D7P-10**

Order No. 0173370

10 m**Extension cable**

- 7-pole DIN plug to 7-pole DIN jack
- Length: 10 m

**D7P-20**

Order No. 0173380

20 m**Extension cable**

- 7-pole DIN plug to 7-pole DIN jack
- Length: 20 m

