

## Conference System CS-1

Your opinion will be heard! The control unit CS-1CU, the microphone station for the chairperson CS-1CH and the microphone station for conference delegates CS-1DU together form a conference system with extensive configuration facilities for maximum flexibility.

### CS-1CU

Order No. 0173060

#### Control unit, the control centre of the conference system

- For setting up a system with up to 50 microphone stations (2 x 25)
- Power supply for microphone stations
- Built-in speaker
- Headphone connection
- Keypad lock
- Display of date/time
- Stopwatch
- Test function for connected microphone stations
- Connection facilities for optional devices, e.g. external microphone, telephone coupler, signal processing units (e.g. equalizer), recorders, amplifiers, audio line sources

Model	CS-1CU
Dimensions	360 x 90 x 150 mm
Weight	1.7 kg
Connections	2 x RCA (input/output for telephone coupler) 2 x RCA (input/output, e.g. for equalizer) 2 x RCA L/R (input/output for recorder) 2 x RCA (input/output for line signals) 1 x XLR (microphone input) 2 x 7-pole DIN jack (connection for microphone stations)



### CS-1CH

Order No. 0173070

#### Microphone station for chairperson

- Back electret cartridge with cardioid polar pattern, optimised for voice transmissions
- Low-distortion speaker
- Reproduction via optional headphones
- Large function button
- Status displays at microphone and desktop station
- Priority button allows to interrupt an ongoing discussion between conference delegates, alternatively with a chime

Model	CS-1CH
Polar pattern	cardioid
System	back electret
Audio frequency range	50-18,000 Hz
Power supply	via control unit CS-1CU
Gooseneck length	400 mm
Dimensions	115 x 65 x 170 mm (console housing)
Weight	1.1 kg
Connection	2 x 3.5 mm jack 1 x 2 m connection cable with 7-pole DIN plug 1 x 7-pole DIN jack



### CS-1DU

Order No. 0173080

#### Microphone station for conference delegates

- Back electret cartridge with cardioid polar pattern, optimised for voice transmissions
- Low-distortion speaker
- Operation via function button
- Headphone connection
- Status displays at microphone and desktop station

Model	CS-1DU
Polar pattern	cardioid
System	back electret
Audio frequency range	50-18,000 Hz
Power supply	via control unit CS-1CU
Gooseneck length	400 mm
Dimensions	115 x 65 x 170 mm (console housing)
Weight	1.1 kg
Connection	2 x 3.5 mm jack 1 x 2 m connection cable with 7-pole DIN plug 1 x 7-pole DIN jack



### D7P-10

Order No. 0173370

10 m

#### Extension cable

- 7-pole DIN plug to 7-pole DIN jack
- Length: 10 m



### D7P-20

Order No. 0173380

20 m

#### Extension cable

- 7-pole DIN plug to 7-pole DIN jack
- Length: 20 m

