

PD-206M

ตอบสนองทุกความต้องการของท่านบรรยาย...



แท่นบรรยายขยายเสียงที่มีชุดเล่นและบันทึกเสียงระบบดิจิทัล MP3 (Podium Amplifier With MP3 Player Bluetooth & Recorder)

- ใช้สำหรับการประชุม บรรยาย หรือกล่าวสุนทรพจน์ มีอุปกรณ์ให้ครบครัน
- มีเครื่องขยายเสียง 40 W พร้อมลำโพงคู่ (6") ในตัว
- มีไมโครโฟนคออ่อนสามารถปรับโค้งงอและถอดเก็บได้ ความยาว 56 เซนติเมตร
- มีเครื่องเล่นไฟล์ MP3 และบันทึกเสียงได้ในตัว พร้อมรีโมทคอนโทรล
- มีช่องเสียบ USB และสามารถเชื่อมต่อ Bluetooth ได้
- ตัวโครงสร้างประกอบด้วยอลูมิเนียมน้ำหนักเบา สามารถถอดถอดวางเอกสารและฐานตั้งเครื่องได้
- ถอดวางเอกสารสามารถปรับเอียงมุมได้ 4 ระดับ
- มีหูจับสำหรับหิ้วเคลื่อนย้ายได้สะดวก
- มีช่องใช้งานภายนอก MIC In 1 ช่อง, AUX In 1 ช่อง, Pre Out 1 ช่อง และ DC Out 12 V สำหรับไมโครโฟนสาย
- มีช่องต่อหลอดไฟส่องสว่าง 12 Vdc พร้อมปุ่ม เปิด - ปิด
- ปุ่มปรับความดังแยกอิสระพร้อมปุ่มโทนคอนโทรล
- MADE IN THAILAND

SPECIFICATIONS : (PD-206M)

Frequency Response: @ 0, -3 dB MIC 1 Input (@ +1, -2 dB) MIC 2 Input AUX Input MP3 Player Recorder	20 Hz - 20 kHz 50 Hz - 18 kHz 20 Hz - 20 kHz 25 Hz - 19 kHz 50 Hz - 15 kHz
Distortion (THD + N): @ 1 kHz All Input to Pre Output All Input to Amp Output @ 4 Ω	< 0.1% < 1%
Tone Control:	± 10 dB @ 7 kHz Shelving
Input Sensitivity: MIC 1 Input MIC 2 Input AUX Input	-31 dBu -48 dBu -10 dBu
Output: Power Amplifier @ 4 Ω Pre Out	40 Wrms 0 dBu
Speaker: Frequency Response @ ± 3 dB	50 Hz - 12 kHz (6" 8 Ω x 2)
Input Impedance / Type: MIC 1 (Goose Neck) Input MIC 2 Input AUX Input	2 kΩ / Unbalanced 3.4 kΩ / Balanced 8 kΩ / Unbalanced
Hum & Noise: MIC 1 Input MIC 2 Input AUX Input	< -41 dBu < -35 dBu < -44 dBu
MP3 Player / Recorder: Input Source Recorder	USB MP3, Bluetooth, USB DAC Low (48 kbps), High (128 kbps)
DC Output & Lamp Voltage:	12 Vdc
LED Indication:	On
Power: Requirement Consumption: Idle / Rate @ 4 Ω	220 Vac 50 Hz 11 W / 96 W
Dimensions : (W x H x D) Column: Packing Stand & Base: Packing	560 x 1,223 x 440 mm 332 x 265 x 1,151 mm 495 x 170 x 611 mm
Net Weight / Gross Weight: Column: Gross Weight Stand & Base: Gross Weight	23.94 kg (52.67 lbs) / 27.88 kg (61.34 lbs) 16.60 kg (36.52 lbs) 11.28 kg (24.82 lbs)

Note: 0dBu=0.775Vrms, 0dBV=1Vrms

All features & specifications subject to change without notice. © NPE Industry (Thailand) Co.,Ltd (R1) 26 April 2025