

H-9500M Central Unit



Description



Based on digital control technologies, this series full digital conference system is flexible and reliable for any mini/medium/large conference. This system main features include microphone management, automatic video tracking, conference audio recording, voting, etc.

This series full digital conference system is also provided with function that to access and control main unit through software, thus the operator can easily manage and control the conference proceedings.

Other peripheral devices like computers, touch panels, projectors and loudspeakers can also be integrated with H-9500 series fully digital conference system

Features

- FTP CAT6 cables are introduced for data transmission and power supply, supporting message transmission with a fast internet service of 100M. Thus audio signals could be delivered perfectly in long distance.
- 80 pieces of microphones could be applied simultaneously on single conference system, with H-9500E digital conference extension unit, totally 400 microphones can be connected to the system. This digital conference system has four network interfaces (RJ45), each of them allows the connection of twenty microphones. Four microphones are allowed to be activated at the same time.
- A sampling frequency of 48KHZ is supported by the system.
- In order to ensure clear, highly sensitive, and perfect sound quality, high-performance dual-core CPU, 32 bit high-speed digital signal processing, audio feedback inhibition, acoustic echo cancelling, noise reduction and digital equalization are available.
- TCP (transmission control protocol) and IP (internet protocol) are available, enabling a reliable and safe management.
- LCD screen that displays the operating status of various functions.
- When coupled with phone coupler, teleconference could be realized.
- Video tracking control unit and high-definition switching matrix are available for high definition auto video tracking.
- Built-in USB storage, allowing the realizing of recording and monitoring.
- Audio signal can be output both in balanced and unbalanced for connecting other audio equipments such as mixer, mixing amplifier etc.
- Different interfaces provided, like Ethernet, RS422 and RS232, can meet different devices requirement.

H-9500M Central Unit



Features

- Three modes available: REQUEST(1-4), LIMIT (1-4), and FIFO (1-4), support speech timing function.
- Multiple conference functions can be realized when the digital conference system is connected to computers via cables.
- Connection: FTP CAT6 Ethernet cable
- Control interface. : 9 PIN, D-type (female), connecting to the central control system (RS232C)
RJ45 Ethernet, connecting to PC
RS422, connecting to high speed dome camera

Technical Specification

| | |
|--------------------|--|
| Power Supply | AC 220V-240V (50Hz/60Hz) |
| Power Consumption | 300W |
| T.H.D. | <0.05% |
| S/N | >80dB |
| Frequency Response | 20Hz-20KHz |
| Color | Black |
| Audio Input Port | RCAx1, XLR x1 |
| Audio Output Port | RCAx1, XLRx1 |
| Audio Output level | +18dBu balanced |
| Output Voltage | DC24V |
| Control Interface | 9 PIN, D-type (female), connecting the central control system main unit (RS232C) RJ45 Ethernet, connecting to PC RS422, connecting to high speed dome camera |
| Connector | RJ45x4 |
| Connection Cable | FTP Cat6 Ethernet cable |
| Dimension (mm) | 483x360x88 |
| Net Weight (Kg) | 7.6 kg. |
| Installation | 2U rack, 19 inch frame |