Zone Paging Microphone

NPE® AUDIO PRODUCTS

CM – 1000Z



Specifications :	CM-1000Z
Microphone:	
Design	46 cm Gooseneck with LED & XLR3 - M
Type	Unidirectional Condenser Cartridge
Connector	XLR3 - F (1 G, 2 + , 3 LED)
Sensitivity	-24 dBu
Frequency Response	80 Hz – 15 kHz 0, -3 dB
THD + N	< 0.007 %
Hum & Noise	< -102 dBu
Chime 4 Tone:	
Talk On Frequency	440, 554, 659, 880 Hz
Talk Off Frequency	880, 659, 554, 440 Hz
MP3 Player:	
Frequency Response	50 Hz – 20 kHz 0, - 3 dB
THD	< 0.3 %
Bluetooth Device Name / Range	MIX - MP3 - BT / 10 m
PC USB Device Driver	Jieli BR21
MP3 USB Equalizer Mode	Natural, Rock, Pop, Classic, Jazz, Country
Output:	
Connector	XLR3 - M, Phones 1 / 8" TRS Jack
Mic / Chime Level	-10 dBu Balanced
Phones / Record Level	15 mW @ 16 Ω / 12 dBu @ 100 kΩ
Cable	1.5 m XLR - Female to 1 / 4" TRS Plug
Zone Selection:	2 Zone A 1-5 / B 6-10
Communication Protocol:	RS - 485
Communication Interface:	RJ45
Link cable length:	100 m LAN CAT5E
Other Selection:	ALL ON / ALL OFF
Power:	
Connector	DC Jack in Ø 2 mm
Requirement	Adaptor 220 Vac to 15 Vac / 20 Vdc 1000 mA
Consumption	7.5 W
Dimensions / Packing Dimensions: (W X H X D)	220 x 69 x 182 mm / 490 x 100 x 208 mm
Net Weight / Gross Weight:	2.58 kg (5.68 lbs) / 2.98 kg (6.56 lbs)

Note: 0dBu=0.775Vrms, 0dBV=1Vrms

คุณสมบัติ

- ไมค์ประกาศเสียงแบบตั้งโต๊ะ พร้อมเครื่องเล่น BLUETOOTH / PC / MP3 ในตัว และสามารถเป็นรีโมทควบคุมการทำงานเครื่องรุ่น DSL-10Z ระยะไกลได้
- สวิตช์ เปิด - ปิด ไมค์พูดพร้อมเสียงระฆัง 4 โทน และตัดต่อเสียง MP3 อัตโนมัติ
- ช่องต่อ Output แบบ Balanced XLR และหูฟัง / Record ชนิด 1 / 8" TRS Jack
- กำหนดโซนการทำงานได้ 2 Input 10 Output (Zone A, Zone B) พร้อมไฟ LED แสดงสถานะการทำงานเชื่อมต่อโซน
- ไมโครโฟนชนิดคออ่อนความยาว 46 cm. ถอดเปลี่ยนได้ มีแสงรอบวงที่คอไมค์
- มีปุ่มปรับความดังเสียงระฆัง, ไมค์, BLUETOOTH / MP3 และหูฟังแยกอิสระ
- สามารถควบคุมการทำงานระยะไกลผ่านสาย LAN CAT5E ขั้วต่อแบบ RJ45 ความยาวได้สูงสุด 100 เมตร